


UKW 2-1-E R290 Forced air cooling wells: self-contained



€5,101.00

plus VAT

Item no.: EU253701



Completely made of stainless steel
All visible sides polished
Inner well welded tight in a hygienic design
Polyurethane rigid foam insulation (compression-moulded)
Coated fin coil evaporator with circulating air – can be folded up for cleaning
Electronic controller with digital temperature display
Fully-automatic defrosting
Deep-drawn condensate drain HD 30

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT

☎ +43 7612 660 61

✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT

☎ +43 3624 211 00

✉ office@ake.at

Width:	725
Depth:	660
Height:	655
Version:	E
Power input cold:	151 Watt
Installation Opening width:	735
Installation Opening depth:	665
Inner well width:	655
Inner well depth:	535
Inner well height:	175
Annual energy consumption kWh:	1113,2500
Energy efficiency index:	56,2830
Voltage volt:	230V
Frequency Hz:	50Hz
Refrigeration :	R290
Cooling capacity:	340 Watt at VT -6°C
Energy efficiency class :	E
Temperature class:	M2 -1 +7
Energy consumption kWh 24h:	3,0500
Refrigerated display case Climate class:	3
Standard:	EN ISO 23953-2

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
 ☎ +43 7612 660 61
 ✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
 ☎ +43 3624 211 00
 ✉ office@ake.at