

Euro 4-Z Forced air cooling wells: remote cooling



€5,739.00

plus VAT

Item no.: EU253881



Completely made of stainless steel
All visible sides polished
Inner well welded tight in a hygienic design
Polyurethane rigid foam insulation (compression-moulded)
Coated fin coil evaporator with circulating air – can be folded up for cleaning
Electronic controller with digital temperature display
Fully-automatic defrosting
Deep-drawn condensate drain HD 30

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
☎ +43 7612 660 61
✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
☎ +43 3624 211 00
✉ office@ake.at

Width:	1690
Depth:	735
Height:	390
Version:	Z
Power input cold:	15 Watt
Installation Opening width:	1700
Installation Opening depth:	740
Inner well width:	1620
Inner well depth:	610
Inner well height:	175
Net content liters:	178
Annual energy consumption kWh:	1600,4520
Energy efficiency index:	61,2513
Voltage volt:	230
Frequency Hz:	50
Refrigeration :	R134a
Cooling capacity:	700 Watt at VT -6°C
Energy efficiency class :	E
Temperature class:	M2 -1 +7
Energy consumption kWh 24h:	4,3848
Refrigerated display case Climate class:	3
Standard:	EN ISO 23953-2

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
 ☎ +43 7612 660 61
 ✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
 ☎ +43 3624 211 00
 ✉ office@ake.at