Gastro GE-78-45-Z EC PRO Built-in refrigerated display case EC: remote cooling



€6,031.00

plus VAT

Item no.: EU330626

Glass enclosure: squared design with normal glazingPRO version: Outer body flush and polished, suitable for protruding installation.Completely made of stainless steel
all visible sides polished
Inner well welded tight in a hygienic design
Polyurethane rigid foam insulation (compression-moulded)
coated fin coil evaporator with circulating air – can be folded up for cleaning
speed-controlled low-voltage fan
electronic controller with digital temperature display
fully-automatic defrosting
deep-drawn condensate drain HD 30
cleaning-friendly glass enclosure
interior lighting on each level

Typing and database errors reserved.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at

Modell:	PRO square
Width:	775
Depth:	695
Height:	824
Version:	Z
Power input cold:	59 Watt
Installation Opening width:	740
Installation Opening depth:	670
Inner well width:	655
Inner well depth:	535
Inner well height:	215
Voltage volt:	230
Frequency Hz:	50
Refrigeration :	R134a
Cooling capacity:	390 Watt at VT -10°C
Energy consumption kWh 24h:	17,7600

Typing and database errors reserved.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at