

Gastro GE-177-70-E Built-in refrigerated display case: self-contained



€10,889.00

plus VAT

Item no.: EU331063

Glass enclosure: squared design with normal glazing Completely made of stainless steel
all visible sides polished
Inner well welded tight in a hygienic design
Polyurethane rigid foam insulation (compression-moulded)
coated fin coil evaporator with circulating air – can be folded up for cleaning
speed-controlled low-voltage fan
electronic controller with digital temperature display
fully-automatic defrosting
deep-drawn condensate drain HD 30
interior lighting on each level
cleaning-friendly glass enclosure

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
☎ +43 7612 660 61
✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
☎ +43 3624 211 00
✉ office@ake.at

Modell:	squared
Width:	1775
Depth:	695
Height:	1420
Version:	E
Power input cold:	541 Watt
Installation Opening width:	1715
Installation Opening depth:	670
Inner well width:	1630
Inner well depth:	535
Inner well height:	215
Voltage volt:	230
Frequency Hz:	50
Refrigeration :	R134a
Cooling capacity:	720 Watt at VT -10°C
Energy consumption kWh 24h:	21,9400

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
☎ +43 7612 660 61
✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
☎ +43 3624 211 00
✉ office@ake.at