

Gastro AE-145-65-Z Countertop refrigerated display case: remote cooling





plus VAT

Item no.: EU331257

Glass enclosure: squared design with normal glazingCompletely made of stainless steel all visible sides polished Inner well welded tight in a hygienic design Polyurethane rigid foam insulation (compression-moulded) coated fin coil evaporator with circulating air – can be folded up for cleaning speed-controlled low-voltage fan electronic controller with digital temperature display fully-automatic defrosting deep-drawn condensate drain HD 30 interior lighting on each level cleaning-friendly glass enclosure

Modell:	squared
Version:	Z
Power input cold:	109 Watt
Inner well width:	1360
Inner well depth:	445
Inner well height:	15
Voltage volt:	230
Frequency Hz:	50
Refrigeration :	R134a
Cooling capacity:	390 Watt at VT -10°C
Energy consumption kWh 24h:	7,2200

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

◊ In der Schörihub 28, 4810 Gmunden, AT
 ∞ +43 7612 660 61
 ∞ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH Pichl 66, 8984 Bad Mitterndorf, AT # +43 3624 211 00 # office@ake.at