

## BAK GS-132-70-Z Built-in refrigerated display case: remote cooling



**€7,133.00**

plus VAT

**Item no.:** EU332167



Glass enclosure: oblique design with normal glazing Completely made of stainless steel  
all visible sides polished  
Inner well welded tight in a hygienic design  
Polyurethane rigid foam insulation (compression-moulded)  
coated fin coil evaporator with circulating air – can be folded up for cleaning  
speed-controlled low-voltage fan  
electronic controller with digital temperature display  
fully-automatic defrosting  
deep-drawn condensate drain HD 30  
interior lighting on each level  
cleaning-friendly glass enclosure

Typing and database errors reserved.

**IDEAL Kältetechnik GmbH**

📍 In der Schörihub 28, 4810 Gmunden, AT  
☎ +43 7612 660 61  
✉ office@ideal-ake.at

**AKE Ausseer Kälte- und Edelstahltechnik GmbH**

📍 Pichl 66, 8984 Bad Mitterndorf, AT  
☎ +43 3624 211 00  
✉ office@ake.at

|                                          |                      |
|------------------------------------------|----------------------|
| Modell:                                  | inclined             |
| Width:                                   | 1325                 |
| Depth:                                   | 770                  |
| Height:                                  | 895                  |
| Version:                                 | Z                    |
| Power input cold:                        | 103 Watt             |
| Installation Opening width:              | 1305                 |
| Installation Opening depth:              | 745                  |
| Inner well width:                        | 1215                 |
| Inner well depth:                        | 610                  |
| Inner well height:                       | 40                   |
| Annual energy consumption kWh:           | 1587,7500            |
| Energy efficiency index:                 | 32,7355              |
| Voltage volt:                            | 230                  |
| Frequency Hz:                            | 50                   |
| Refrigeration :                          | R134a                |
| Cooling capacity:                        | 590 Watt at VT -10°C |
| Energy efficiency class :                | C                    |
| Temperature class:                       | H1 +1 +10            |
| Energy consumption kWh 24h:              | 4,3500               |
| Refrigerated display case Climate class: | 3                    |
| Standard:                                | EN ISO 23953-2       |

Typing and database errors reserved.

#### IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT  
 ☎ +43 7612 660 61  
 ✉ office@ideal-ake.at

#### AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT  
 ☎ +43 3624 211 00  
 ✉ office@ake.at