Gastro AS-145-65-E Countertop refrigerated display case: self-contained



€7,802.00

plus VAT

Item no.: EU332252

Glass enclosure: oblique design with normal glazingCompletely made of stainless steel
all visible sides polished
Inner well welded tight in a hygienic design
Polyurethane rigid foam insulation (compression-moulded)
coated fin coil evaporator with circulating air – can be folded up for cleaning
speed-controlled low-voltage fan
electronic controller with digital temperature display
fully-automatic defrosting
deep-drawn condensate drain HD 30
interior lighting on each level
cleaning-friendly glass enclosure

Typing and database errors reserved.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at

Modell:	inclined
Width:	1450
Depth:	810
Height:	655
Version:	E
Power input cold:	355 Watt
Inner well width:	1360
Inner well depth:	445
Inner well height:	15
Voltage volt:	230
Frequency Hz:	50
Refrigeration :	R134a
Cooling capacity:	390 Watt at VT -10°C

Typing and database errors reserved.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at