

## Gastro AS-145-65-Z Countertop refrigerated display case: remote cooling



**€6,091.00**

plus VAT

**Item no.:** EU332257

Glass enclosure: oblique design with normal glazing Completely made of stainless steel  
all visible sides polished

Inner well welded tight in a hygienic design

Polyurethane rigid foam insulation (compression-moulded)

coated fin coil evaporator with circulating air – can be folded up for cleaning

speed-controlled low-voltage fan

electronic controller with digital temperature display

fully-automatic defrosting

deep-drawn condensate drain HD 30

interior lighting on each level

cleaning-friendly glass enclosure

Modell:	inclined
Version:	Z
Power input cold:	109 Watt
Inner well width:	1360
Inner well depth:	445
Inner well height:	15
Voltage volt:	230
Frequency Hz:	50
Refrigeration :	R134a
Cooling capacity:	390 Watt at VT -10°C
Energy consumption kWh 24h:	5,3500

Typing and database errors reserved.

**IDEAL Kältetechnik GmbH**

📍 In der Schörihub 28, 4810 Gmunden, AT

☎ +43 7612 660 61

✉ office@ideal-ake.at

**AKE Ausseer Kälte- und Edelstahltechnik GmbH**

📍 Pichl 66, 8984 Bad Mitterndorf, AT

☎ +43 3624 211 00

✉ office@ake.at