


BAK GE-92-53-Z PRO Built-in refrigerated display case: remote cooling



€5,676.00

plus VAT

Item no.: EU334156



Glass enclosure: squared design with normal glazing
PRO version: Outer body flush and polished, suitable for protruding installation. Completely made of stainless steel
all visible sides polished
Inner well welded tight in a hygienic design
Polyurethane rigid foam insulation (compression-moulded)
coated fin coil evaporator with circulating air – can be folded up for cleaning
speed-controlled low-voltage fan
electronic controller with digital temperature display
fully-automatic defrosting
deep-drawn condensate drain HD 30
cleaning-friendly glass enclosure
interior lighting on each level

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
☎ +43 7612 660 61
✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
☎ +43 3624 211 00
✉ office@ake.at

Modell:	PRO square
Width:	910
Depth:	770
Height:	725
Version:	Z
Power input cold:	72 Watt
Installation Opening width:	900
Installation Opening depth:	745
Inner well width:	810
Inner well depth:	610
Inner well height:	40
Annual energy consumption kWh:	1332,2500
Energy efficiency index:	33,0660
Voltage volt:	230
Frequency Hz:	50
Refrigeration :	R134a
Cooling capacity:	520 Watt at VT -10°C
Energy efficiency class :	C
Temperature class:	H1 +1 +10
Energy consumption kWh 24h:	3,6500
Refrigerated display case Climate class:	3
Standard:	EN ISO 23953-2

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
 ☎ +43 7612 660 61
 ✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
 ☎ +43 3624 211 00
 ✉ office@ake.at