

Gastro HCOE-112-87-Z Built-in refrigerated display case: remote cooling



€10,544.00

plus VAT

Item no.: EU341166

Glass enclosure: squared design with double-glazing on the side Completely made of stainless steel
all visible sides polished
Inner well welded tight in a hygienic design
Polyurethane rigid foam insulation (compression-moulded)
coated fin coil evaporator with circulating air – can be folded up for cleaning
speed-controlled low-voltage fan
electronic controller with digital temperature display
fully-automatic defrosting
deep-drawn condensate drain HD 30
interior lighting on each level
cleaning-friendly glass enclosure
PRO version: Outer body flush and polished, suitable for protruding installation.

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
☎ +43 7612 660 61
✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
☎ +43 3624 211 00
✉ office@ake.at

Modell:	squared
Width:	1125
Depth:	770
Height:	1235
Version:	Z
Power input cold:	439 Watt
Installation Opening width:	1065
Installation Opening depth:	745
Inner well width:	980
Inner well depth:	610
Inner well height:	155
Voltage volt:	230
Frequency Hz:	50
Refrigeration :	R452A
Cooling capacity:	1620 Watt at VT -10°C
Energy consumption kWh 24h:	6,4200

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT

☎ +43 7612 660 61

✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT

☎ +43 3624 211 00

✉ office@ake.at