

Gastro GS-112-53-Z KL Built-in refrigerated display case: remote cooling



€6,652.00

plus VAT

Item no.: EU342256

Glass enclosure: oblique design with normal glazing Completely made of stainless steel
all visible sides polished
Inner well welded tight in a hygienic design
Polyurethane rigid foam insulation (compression-moulded)
coated fin coil evaporator with circulating air – can be folded up for cleaning
speed-controlled low-voltage fan
electronic controller with digital temperature display
fully-automatic defrosting
deep-drawn condensate drain HD 30
interior lighting on each level
cleaning-friendly glass enclosure

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
☎ +43 7612 660 61
✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
☎ +43 3624 211 00
✉ office@ake.at

Modell:	inclined
Width:	1125
Depth:	695
Height:	900
Version:	Z
Power input cold:	80 Watt
Installation Opening width:	1065
Installation Opening depth:	670
Inner well width:	980
Inner well depth:	535
Inner well height:	215
Number of removal flaps:	6
Voltage volt:	230
Frequency Hz:	50
Refrigeration :	R134a
Cooling capacity:	520 Watt at VT -10°C

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
☎ +43 7612 660 61
✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
☎ +43 3624 211 00
✉ office@ake.at