

Green OR-145-70-Z RG Built-in refrigerated display case: remote cooling



€11,368.00

plus VAT

Item no.: EU350217



Glass enclosure: round design with double-glazing on the side
 all visible sides polished
 Inner well welded tight in a hygienic design
 Polyurethane rigid foam insulation (compression-moulded)
 coated fin coil evaporator with circulating air – can be folded up for cleaning
 speed-controlled low-voltage fan
 electronic controller with digital temperature display
 fully-automatic defrosting
 deep-drawn condensate drain HD 30
 interior lighting on each level
 cleaning-friendly glass enclosure
 PRO version: Outer body flush and polished, suitable for protruding installation.

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
 ☎ +43 7612 660 61
 ✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
 ☎ +43 3624 211 00
 ✉ office@ake.at

Modell:	curved
Width:	1450
Depth:	695
Height:	1090
Version:	Z
Power input cold:	211 Watt
Installation Opening width:	1390
Installation Opening depth:	670
Inner well width:	1305
Inner well depth:	535
Inner well height:	215
Annual energy consumption kWh:	5876,5000
Energy efficiency index:	78,2693
Voltage volt:	230
Frequency Hz:	50
Refrigeration :	R452A
Cooling capacity:	1500 Watt at VT -10°C
Energy efficiency class :	F
Temperature class:	M1 -1 +5
Energy consumption kWh 24h:	16,1000
Refrigerated display case Climate class:	3
Standard:	EN ISO 23953-2

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
 ☎ +43 7612 660 61
 ✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
 ☎ +43 3624 211 00
 ✉ office@ake.at