

Green OE-112-70-Z Built-in refrigerated display case: remote cooling



€9,855.00

plus VAT

Item no.: EU351186



Glass enclosure: squared design with double-glazing on the side Completely made of stainless steel
all visible sides polished
Inner well welded tight in a hygienic design
Polyurethane rigid foam insulation (compression-moulded)
coated fin coil evaporator with circulating air – can be folded up for cleaning
speed-controlled low-voltage fan
electronic controller with digital temperature display
fully-automatic defrosting
deep-drawn condensate drain HD 30
interior lighting on each level
cleaning-friendly glass enclosure
PRO version: Outer body flush and polished, suitable for protruding installation.

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
☎ +43 7612 660 61
✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
☎ +43 3624 211 00
✉ office@ake.at

Modell:	squared
Width:	1125
Depth:	695
Height:	1090
Version:	Z
Power input cold:	166 Watt
Installation Opening width:	1065
Installation Opening depth:	670
Inner well width:	980
Inner well depth:	535
Inner well height:	215
Raumtemperatur:	max. 24 °C und rel. LF 55%
Annual energy consumption kWh:	4752,3000
Energy efficiency index:	79,5446
Voltage volt:	230
Frequency Hz:	50
Refrigeration :	R452A
Cooling capacity:	1360 Watt at VT -10°C
Temperature range:	+5 °C bis +8 °C
Energy efficiency class :	F
Temperature class:	M2 -1 +7
Energy consumption kWh 24h:	13,0200
Refrigerated display case Climate class:	3
Standard:	EN ISO 23953-2

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
 ☎ +43 7612 660 61
 ✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
 ☎ +43 3624 211 00
 ✉ office@ake.at