

## Green OR-112-70-Z RG PRO Built-in refrigerated display case: remote cooling



**€10,352.00**

plus VAT

**Item no.:** EU353216



Glass enclosure: round design with double-glazing on the side Completely made of stainless steel  
all visible sides polished  
Inner well welded tight in a hygienic design  
Polyurethane rigid foam insulation (compression-moulded)  
coated fin coil evaporator with circulating air – can be folded up for cleaning  
speed-controlled low-voltage fan  
electronic controller with digital temperature display  
fully-automatic defrosting  
deep-drawn condensate drain HD 30  
interior lighting on each level  
cleaning-friendly glass enclosure  
PRO version: Outer body flush and polished, suitable for protruding installation.

Typing and database errors reserved.

**IDEAL Kältetechnik GmbH**

📍 In der Schörihub 28, 4810 Gmunden, AT  
☎ +43 7612 660 61  
✉ office@ideal-ake.at

**AKE Ausseer Kälte- und Edelstahltechnik GmbH**

📍 Pichl 66, 8984 Bad Mitterndorf, AT  
☎ +43 3624 211 00  
✉ office@ake.at

|                                          |                       |
|------------------------------------------|-----------------------|
| Modell:                                  | PRO curved            |
| Width:                                   | 1115                  |
| Depth:                                   | 695                   |
| Height:                                  | 1090                  |
| Version:                                 | Z                     |
| Power input cold:                        | 166 Watt              |
| Installation Opening width:              | 1065                  |
| Installation Opening depth:              | 670                   |
| Inner well width:                        | 980                   |
| Inner well depth:                        | 535                   |
| Inner well height:                       | 215                   |
| Annual energy consumption kWh:           | 4624,5500             |
| Energy efficiency index:                 | 68,0667               |
| Voltage volt:                            | 230                   |
| Frequency Hz:                            | 50                    |
| Refrigeration :                          | R452A                 |
| Cooling capacity:                        | 1360 Watt at VT -10°C |
| Energy efficiency class :                | F                     |
| Temperature class:                       | M1 -1 +5              |
| Energy consumption kWh 24h:              | 12,6700               |
| Refrigerated display case Climate class: | 3                     |
| Standard:                                | EN ISO 23953-2        |

Typing and database errors reserved.

#### IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT  
 ☎ +43 7612 660 61  
 ✉ office@ideal-ake.at

#### AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT  
 ☎ +43 3624 211 00  
 ✉ office@ake.at