

Green GR-80-54-Z PRO Built-in refrigerated display case: remote cooling



€5,723.00

plus VAT

Item no.: EU353355

Glass enclosure: round design with double-glazing PRO version: Outer body flush and polished, suitable for protruding installation. Completely made of stainless steel

all visible sides polished

Inner well welded tight in a hygienic design

Polyurethane rigid foam insulation (compression-moulded)

coated fin coil evaporator with circulating air – can be folded up for cleaning

speed-controlled low-voltage fan

electronic controller with digital temperature display

fully-automatic defrosting

deep-drawn condensate drain HD 30

cleaning-friendly glass enclosure

interior lighting on each level

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT

☎ +43 7612 660 61

✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT

☎ +43 3624 211 00

✉ office@ake.at

Modell:	PRO curved
Version:	Z
Power input cold:	66 Watt
Installation Opening width:	740
Installation Opening depth:	670
Inner well width:	655
Inner well depth:	535
Inner well height:	215
Voltage volt:	230
Frequency Hz:	50
Refrigeration :	R134a
Cooling capacity:	390 Watt at VT -10°C

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
☎ +43 7612 660 61
✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
☎ +43 3624 211 00
✉ office@ake.at