


Green OR-80-53-Z PRO Built-in refrigerated display case: remote cooling



€8,281.00

plus VAT

Item no.: EU355080



Glass enclosure: round design with double-glazing on the side Completely made of stainless steel
all visible sides polished

Inner well welded tight in a hygienic design

Polyurethane rigid foam insulation (compression-moulded)

coated fin coil evaporator with circulating air – can be folded up for cleaning

speed-controlled low-voltage fan

electronic controller with digital temperature display

fully-automatic defrosting

deep-drawn condensate drain HD 30

interior lighting on each level

cleaning-friendly glass enclosure

PRO version: Outer body flush and polished, suitable for protruding installation.

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT

☎ +43 7612 660 61

✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT

☎ +43 3624 211 00

✉ office@ake.at

Modell:	PRO curved
Width:	790
Depth:	695
Height:	920
Version:	Z
Power input cold:	86 Watt
Installation Opening width:	740
Installation Opening depth:	670
Inner well width:	655
Inner well depth:	535
Inner well height:	215
Annual energy consumption kWh:	2865,2500
Energy efficiency index:	62,8699
Voltage volt:	230
Frequency Hz:	50
Refrigeration :	R452A
Cooling capacity:	960 Watt at VT -10°C
Energy efficiency class :	E
Temperature class:	M2 -1 +7
Energy consumption kWh 24h:	7,8500
Refrigerated display case Climate class:	3
Standard:	EN ISO 23953-2

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
 ☎ +43 7612 660 61
 ✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
 ☎ +43 3624 211 00
 ✉ office@ake.at