
Green OE-145-53-Z RG PRO Built-in refrigerated display case: remote cooling



€10,850.00

plus VAT

Item no.: EU355097



Glass enclosure: squared design with double-glazing on the sideCompletely made of stainless steel all visible sides polished
Inner well welded tight in a hygienic design
Polyurethane rigid foam insulation (compression-moulded)
coated fin coil evaporator with circulating air – can be folded up for cleaning
speed-controlled low-voltage fan
electronic controller with digital temperature display
fully-automatic defrosting
deep-drawn condensate drain HD 30
interior lighting on each level
cleaning-friendly glass enclosure
PRO version: Outer body flush and polished, suitable for protruding installation.

Typing and database errors reserved.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at

Modell:	PRO square
Width:	1440
Depth:	695
Height:	920
Version:	Z
Power input cold:	130 Watt
Installation Opening width:	1390
Installation Opening depth:	670
Inner well width:	1305
Inner well depth:	535
Inner well height:	215
Annual energy consumption kWh:	4974,9500
Energy efficiency index:	76,9034
Voltage volt:	230
Frequency Hz:	50
Refrigeration :	R452A
Cooling capacity:	1360 Watt at VT -10°C
Energy efficiency class :	F
Temperature class:	M1 -1 +5
Energy consumption kWh 24h:	13,6300
Refrigerated display case Climate class:	3
Standard:	EN ISO 23953-2

Typing and database errors reserved.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at