

VP 51-Z Built-in Refrigerated Display Case: remote cooling



€5,198.00

plus VAT

Item no.: EU356395



Glass enclosure: squared design with double-glazing
Completely made of stainless steel, all visible sides polished
Inner well welded tight in a hygienic design
Polyurethane rigid foam insulation (compression-moulded)
Coated fin coil evaporator with circulating air – can be folded up for cleaning
Speed-controlled low-voltage fan
Electronic controller with digital temperature display
Fully-automatic defrosting
Deep-drawn condensate drain HD 30
Interior lighting on each level
Cleaning-friendly glass enclosure

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
☎ +43 7612 660 61
✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
☎ +43 3624 211 00
✉ office@ake.at

Width:	515
Depth:	535
Height:	1075
Version:	Z
Power input cold:	57 Watt
Installation Opening width:	495
Installation Opening depth:	495
Inner well width:	410
Inner well depth:	360
Inner well height:	35
Annual energy consumption kWh:	863,9550
Energy efficiency index:	13,4962
Voltage volt:	230V
Frequency Hz:	50Hz
Refrigeration :	R134a
Cooling capacity:	340 Watt at VT -6°C
Energy efficiency class :	B
Temperature class:	M1 -1 +5
Energy consumption kWh 24h:	2,3670
Refrigerated display case Climate class:	3
Standard:	EN ISO 23953-2

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
 ☎ +43 7612 660 61
 ✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
 ☎ +43 3624 211 00
 ✉ office@ake.at