Caleo Cold 60 Freestanding display case: self-contained



€7,987.00

plus VAT

Item no.: EU356600



Freestanding display case
Glass enclosure: oblique design with double-glazing on the side
Completely made of stainless steel, all visible sides polished
Inner well welded tight in a hygienic design
Polyurethane rigid foam insulation (compression-moulded)
Coated fin coil evaporator with circulating air – can be folded up for cleaning
Speed-controlled low-voltage fan
Electronic controller with digital temperature display
Fully-automatic defrosting and condensate evaporation
Deep-drawn condensate drain HD 30
Interior lighting on each level
Price tag railing per shelf

Typing and database errors reserved.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at

Width:	600
Depth:	662
Height:	1410
Version:	E
Power input cold:	480 Watt
Display area width:	497
Display area depth:	436
Annual energy consumption kWh:	2643,1110
Energy efficiency index:	36,9534
Voltage volt:	230V
Frequency Hz:	50Hz
Refrigeration :	R290
Cooling capacity:	851 Watt at VT-6°C
Energy efficiency class :	D
Temperature class:	M1 -1 +5
Energy consumption kWh 24h:	7,2414
Refrigerated display case Climate class:	3
Standard:	EN ISO 23953-2

Typing and database errors reserved.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at