

Caleo Cold 80 Freestanding display case: self-contained



€8,782.00

plus VAT

Item no.: EU356601



Freestanding display case

Glass enclosure: oblique design with double-glazing on the side

Completely made of stainless steel, all visible sides polished

Inner well welded tight in a hygienic design

Polyurethane rigid foam insulation (compression-moulded)

Coated fin coil evaporator with circulating air – can be folded up for cleaning

Speed-controlled low-voltage fan

Electronic controller with digital temperature display

Fully-automatic defrosting and condensate evaporation

Deep-drawn condensate drain HD 30

Interior lighting on each level

Price tag railing per shelf

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

 In der Schörihub 28, 4810 Gmunden, AT

 +43 7612 660 61

 office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

 Pichl 66, 8984 Bad Mitterndorf, AT

 +43 3624 211 00

 office@ake.at

Width:	800
Depth:	662
Height:	1410
Version:	E
Power input cold:	540 Watt
Display area width:	697
Display area depth:	436
Annual energy consumption kWh:	2996,6500
Energy efficiency index:	38,7967
Voltage volt:	230V
Frequency Hz:	50Hz
Refrigeration :	R290
Cooling capacity:	1004 Watt at -6°C
Energy efficiency class :	D
Temperature class:	M1 -1 +5
Energy consumption kWh 24h:	8,2100
Refrigerated display case Climate class:	3
Standard:	EN ISO 23953-2

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
 ☎ +43 7612 660 61
 ✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
 ☎ +43 3624 211 00
 ✉ office@ake.at