

Gastro GS-44-45-Z EC Built-in Refrigerated Display Case EC: remote cooling



€4,669.00

plus VAT

Item no.: EU356675



Glass enclosure: oblique design with normal glazing
Completely made of stainless steel, all visible sides polished
Inner well welded tight in a hygienic design
Polyurethane rigid foam insulation (compression-moulded)
Coated fin coil evaporator with circulating air – can be folded up for cleaning
Speed-controlled low-voltage fan
Electronic controller with digital temperature display
Fully-automatic defrosting
Deep-drawn condensate drain HD 30
Interior lighting on each level
Cleaning-friendly glass enclosure

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
☎ +43 7612 660 61
✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
☎ +43 3624 211 00
✉ office@ake.at

Modell:	inclined
Width:	445
Depth:	695
Height:	824
Version:	Z
Power input cold:	39 Watt
Installation Opening width:	425
Installation Opening depth:	670
Inner well width:	340
Inner well depth:	535
Inner well height:	215
Annual energy consumption kWh:	777,4500
Energy efficiency index:	49,1163
Voltage volt:	230
Frequency Hz:	50
Refrigeration :	R134a
Cooling capacity:	190 Watt at VT -6°C
Energy efficiency class :	D
Temperature class:	M2 -1 +7
Energy consumption kWh 24h:	2,1300
Refrigerated display case Climate class:	3
Standard:	EN ISO 23953-2

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
 ☎ +43 7612 660 61
 ✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
 ☎ +43 3624 211 00
 ✉ office@ake.at