

Gastro GS-145-87-E R290 Built-in Refrigerated Display Case: self-contained



€10,747.00

plus VAT

Item no.: EU357122



Glass enclosure: oblique design with normal glazing
Completely made of stainless steel, all visible sides polished
Inner well welded tight in a hygienic design
Polyurethane rigid foam insulation (compression-moulded)
Coated fin coil evaporator with circulating air – can be folded up for cleaning
Speed-controlled low-voltage fan
Electronic controller with digital temperature display
Fully-automatic defrosting
Deep-drawn condensate drain HD 30
Interior lighting on each level
Cleaning-friendly glass enclosure

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
☎ +43 7612 660 61
✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
☎ +43 3624 211 00
✉ office@ake.at

Modell:	inclined
Width:	1450
Depth:	695
Height:	1554
Version:	E
Power input cold:	408 Watt
Installation Opening width:	1390
Installation Opening depth:	670
Inner well width:	1305
Inner well depth:	535
Inner well height:	215
Annual energy consumption kWh:	2146,2000
Energy efficiency index:	35,4351
Voltage volt:	230
Frequency Hz:	50
Refrigeration :	R290
Cooling capacity:	700 Watt at VT -6°C
Energy efficiency class :	D
Temperature class:	H1 +1 +10
Energy consumption kWh 24h:	5,8800
Refrigerated display case Climate class:	3
Standard:	EN ISO 23953-2

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
 ☎ +43 7612 660 61
 ✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
 ☎ +43 3624 211 00
 ✉ office@ake.at