Gastro HCGS-145-87-Z Built-in Refrigerated Display Case: remote cooling



€9,541.00

plus VAT

Item no.: EU357177



Glass enclosure: oblique design with normal glazing
Completely made of stainless steel, all visible sides polished
Inner well welded tight in a hygienic design
Polyurethane rigid foam insulation (compression-moulded)
Coated fin coil evaporator with circulating air – can be folded up for cleaning
Speed-controlled low-voltage fan
Electronic controller with digital temperature display
Fully-automatic defrosting
Deep-drawn condensate drain HD 30
Interior lighting on each level
Cleaning-friendly glass enclosure

Typing and database errors reserved.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at

Modell:	inclined
Width:	1450
Depth:	770
Height:	1240
Version:	Z
Power input cold:	133 Watt
Installation Opening width:	1390
Installation Opening depth:	745
Inner well width:	1305
Inner well depth:	610
Inner well height:	215
Annual energy consumption kWh:	2763,0500
Energy efficiency index:	47,6256
Voltage volt:	230
Frequency Hz:	50
Refrigeration :	R134a
Cooling capacity:	730 Watt at VT -6°C
Energy efficiency class :	D
Temperature class:	H1 +1 +10
Energy consumption kWh 24h:	7,5700
Refrigerated display case Climate class:	3
Standard:	EN ISO 23953-2

Typing and database errors reserved.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at