


# Gastro HCGR-80-87-Z PRO Built-in Refrigerated Display Case: remote cooling



**€7,525.00**

plus VAT

**Item no.:** EU357185



Glass enclosure: round design with normal glazing  
PRO version: Outer body flush and polished, suitable for protruding installation  
Completely made of stainless steel, all visible sides polished  
Inner well welded tight in a hygienic design  
Polyurethane rigid foam insulation (compression-moulded)  
Coated fin coil evaporator with circulating air – can be folded up for cleaning  
Speed-controlled low-voltage fan  
Electronic controller with digital temperature display  
Fully-automatic defrosting  
Deep-drawn condensate drain HD 30  
Interior lighting on each level  
Cleaning-friendly glass enclosure

Typing and database errors reserved.

**IDEAL Kältetechnik GmbH**

📍 In der Schörihub 28, 4810 Gmunden, AT  
☎ +43 7612 660 61  
✉ [office@ideal-ake.at](mailto:office@ideal-ake.at)

**AKE Ausseer Kälte- und Edelstahltechnik GmbH**

📍 Pichl 66, 8984 Bad Mitterndorf, AT  
☎ +43 3624 211 00  
✉ [office@ake.at](mailto:office@ake.at)

|                                          |                     |
|------------------------------------------|---------------------|
| Modell:                                  | PRO curved          |
| Width:                                   | 790                 |
| Depth:                                   | 770                 |
| Height:                                  | 1240                |
| Version:                                 | Z                   |
| Power input cold:                        | 81 Watt             |
| Inner well width:                        | 655                 |
| Inner well depth:                        | 610                 |
| Inner well height:                       | 215                 |
| Annual energy consumption kWh:           | 1682,6500           |
| Energy efficiency index:                 | 35,5894             |
| Voltage volt:                            | 230                 |
| Frequency Hz:                            | 50                  |
| Refrigeration :                          | R134a               |
| Cooling capacity:                        | 700 Watt at VT -6°C |
| Energy efficiency class :                | D                   |
| Temperature class:                       | H1 +1 +10           |
| Energy consumption kWh 24h:              | 4,6100              |
| Refrigerated display case Climate class: | 3                   |
| Standard:                                | EN ISO 23953-2      |

Typing and database errors reserved.

#### IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT  
 ☎ +43 7612 660 61  
 ✉ office@ideal-ake.at

#### AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT  
 ☎ +43 3624 211 00  
 ✉ office@ake.at