

## BAK GE-51-53-E R290 PRO Built-in Refrigerated Display Case: self-contained



**€5,397.00**

plus VAT

**Item no.:** EU357240



Glass enclosure: squared design with normal glazing  
PRO version: Outer body flush and polished, suitable for protruding installation  
Completely made of stainless steel, all visible sides polished  
Inner well welded tight in a hygienic design  
Polyurethane rigid foam insulation (compression-moulded)  
Coated fin coil evaporator with circulating air – can be folded up for cleaning  
Speed-controlled low-voltage fan  
Electronic controller with digital temperature display  
Fully-automatic defrosting  
Deep-drawn condensate drain HD 30  
Interior lighting on each level  
Cleaning-friendly glass enclosure

Typing and database errors reserved.

**IDEAL Kältetechnik GmbH**

📍 In der Schörihub 28, 4810 Gmunden, AT  
☎ +43 7612 660 61  
✉ office@ideal-ake.at

**AKE Ausseer Kälte- und Edelstahltechnik GmbH**

📍 Pichl 66, 8984 Bad Mitterndorf, AT  
☎ +43 3624 211 00  
✉ office@ake.at

|                                          |                     |
|------------------------------------------|---------------------|
| Modell:                                  | PRO square          |
| Width:                                   | 505                 |
| Depth:                                   | 785                 |
| Height:                                  | 1089                |
| Version:                                 | E                   |
| Power input cold:                        | 193 Watt            |
| Inner well width:                        | 405                 |
| Inner well depth:                        | 610                 |
| Inner well height:                       | 40                  |
| Annual energy consumption kWh:           | 1014,7000           |
| Energy efficiency index:                 | 25,7752             |
| Voltage volt:                            | 230V                |
| Frequency Hz:                            | 50Hz                |
| Refrigeration :                          | R290                |
| Cooling capacity:                        | 340 Watt at VT -6°C |
| Energy efficiency class :                | C                   |
| Temperature class:                       | H1 +1 +10           |
| Energy consumption kWh 24h:              | 2,7800              |
| Refrigerated display case Climate class: | 3                   |
| Standard:                                | EN ISO 23953-2      |

Typing and database errors reserved.

#### IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT  
 ☎ +43 7612 660 61  
 ✉ office@ideal-ake.at

#### AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT  
 ☎ +43 3624 211 00  
 ✉ office@ake.at