

Cold Flaps 70-E Built-in refrigerated display cases with flaps: self-contained



€8,765.00

plus VAT

Item no.: EU357460



Glass enclosure: oblique design with normal glazing
Completely made of stainless steel, all visible sides polished
Inner well welded tight in a hygienic design
Polyurethane rigid foam insulation (compression-moulded)
Coated fin coil evaporator with circulating air – can be folded up for cleaning
Operator side raised – customer side lowered
Speed-controlled low-voltage fan
Electronic controller with digital temperature display
Fully-automatic defrosting and condensate evaporation
Deep-drawn condensate drain HD 30
Interior lighting on each level
Cleaning-friendly glass enclosure
Price tag holder on all presentation levels

Typing and database errors reserved.



Width:	600
Depth:	710
Height:	1335
Version:	E
Power input cold:	252 Watt
Installation Opening width:	580
Installation Opening depth:	670
Inner well width:	490
Inner well depth:	535
Inner well height:	100
Annual energy consumption kWh:	1324,9500
Energy efficiency index:	24,9164
Voltage volt:	230V
Frequency Hz:	50Hz
Refrigeration :	R290
Cooling capacity:	490 Watt at VT -6°C
Energy efficiency class :	C
Temperature class:	H1 +1 +10
Energy consumption kWh 24h:	3,6300
Refrigerated display case Climate class:	3
Standard:	EN ISO 23953-2

Typing and database errors reserved.