

## Green OE-80-89-Z PRO Built-in Refrigerated Display Case: remote cooling



**€9,203.00**

plus VAT

**Item no.:** EU357745



Glass enclosure: squared design with double-glazing on the side  
PRO version: Outer body flush and polished, suitable for protruding installation  
Completely made of stainless steel, all visible sides polished  
Inner well welded tight in a hygienic design  
Polyurethane rigid foam insulation (compression-moulded)  
Coated fin coil evaporator with circulating air – can be folded up for cleaning  
Speed-controlled low-voltage fan  
Electronic controller with digital temperature display  
Fully-automatic defrosting  
Deep-drawn condensate drain HD 30  
Interior lighting on each level  
Cleaning-friendly glass enclosure  
Price tag holder per shelf

Typing and database errors reserved.

**IDEAL Kältetechnik GmbH**

📍 In der Schörihub 28, 4810 Gmunden, AT

☎ +43 7612 660 61

✉ [office@ideal-ake.at](mailto:office@ideal-ake.at)

**AKE Ausseer Kälte- und Edelstahltechnik GmbH**

📍 Pichl 66, 8984 Bad Mitterndorf, AT

☎ +43 3624 211 00

✉ [office@ake.at](mailto:office@ake.at)

|                                          |                      |
|------------------------------------------|----------------------|
| Modell:                                  | PRO square           |
| Width:                                   | 790                  |
| Depth:                                   | 695                  |
| Height:                                  | 1255                 |
| Version:                                 | Z                    |
| Power input cold:                        | 90 Watt              |
| Inner well width:                        | 655                  |
| Inner well depth:                        | 535                  |
| Inner well height:                       | 215                  |
| Annual energy consumption kWh:           | 4504,1000            |
| Energy efficiency index:                 | 77,8530              |
| Voltage volt:                            | 230                  |
| Frequency Hz:                            | 50                   |
| Refrigeration :                          | R452A                |
| Cooling capacity:                        | 960 Watt at VT -10°C |
| Energy efficiency class :                | F                    |
| Temperature class:                       | M2 -1 +7             |
| Energy consumption kWh 24h:              | 12,3400              |
| Refrigerated display case Climate class: | 3                    |
| Standard:                                | EN ISO 23953-2       |

Typing and database errors reserved.

#### IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT  
 ☎ +43 7612 660 61  
 ✉ office@ideal-ake.at

#### AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT  
 ☎ +43 3624 211 00  
 ✉ office@ake.at