

Green OS-80-89-Z RG Built-in Refrigerated Display Case: remote cooling



€8,228.00

plus VAT

Item no.: EU357775



Glass enclosure: oblique design with double-glazing on the side
RG version: Back wall closed in CNS, for installation against a wall
Completely made of stainless steel, all visible sides polished
Inner well welded tight in a hygienic design
Polyurethane rigid foam insulation (compression-moulded)
Coated fin coil evaporator with circulating air – can be folded up for cleaning
Speed-controlled low-voltage fan
Electronic controller with digital temperature display
Fully-automatic defrosting
Deep-drawn condensate drain HD 30
Interior lighting on each level
Cleaning-friendly glass enclosure
Price tag holder per shelf

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

 In der Schörihub 28, 4810 Gmunden, AT
 +43 7612 660 61
 office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

 Pichl 66, 8984 Bad Mitterndorf, AT
 +43 3624 211 00
 office@ake.at

Modell:	inclined
Width:	800
Depth:	695
Height:	1255
Version:	Z
Power input cold:	90 Watt
Installation Opening width:	740
Installation Opening depth:	670
Inner well width:	655
Inner well depth:	535
Inner well height:	215
Annual energy consumption kWh:	4223,0500
Energy efficiency index:	64,1740
Voltage volt:	230
Frequency Hz:	50
Refrigeration :	R452A
Cooling capacity:	1570 Watt at VT -6°C
Energy efficiency class :	E
Temperature class:	M1 -1 +5
Energy consumption kWh 24h:	11,5700
Refrigerated display case Climate class:	3
Standard:	EN ISO 23953-2

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
 ☎ +43 7612 660 61
 ✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
 ☎ +43 3624 211 00
 ✉ office@ake.at