

## Gastro GS-177-87-Z KL Built-in Refrigerated Display Case: remote cooling



**€12,421.00**

plus VAT

**Item no.:** EU357928



Glass enclosure: oblique design with normal glazing  
Customer side: Removal flaps made of acrylic glass;  
Completely made of stainless steel, all visible sides polished  
Inner well welded tight in a hygienic design  
Polyurethane rigid foam insulation (compression-moulded)  
Coated fin coil evaporator with circulating air – can be folded up for cleaning  
Speed-controlled low-voltage fan  
Electronic controller with digital temperature display  
Fully-automatic defrosting  
Deep-drawn condensate drain HD 30  
Interior lighting on each level  
Cleaning-friendly glass enclosure

Typing and database errors reserved.

**IDEAL Kältetechnik GmbH**

📍 In der Schörihub 28, 4810 Gmunden, AT  
☎ +43 7612 660 61  
✉ office@ideal-ake.at

**AKE Ausseer Kälte- und Edelstahltechnik GmbH**

📍 Pichl 66, 8984 Bad Mitterndorf, AT  
☎ +43 3624 211 00  
✉ office@ake.at

|                                          |                     |
|------------------------------------------|---------------------|
| Modell:                                  | inclined            |
| Width:                                   | 1775                |
| Depth:                                   | 695                 |
| Height:                                  | 1240                |
| Version:                                 | Z                   |
| Power input cold:                        | 158 Watt            |
| Installation Opening width:              | 1715                |
| Installation Opening depth:              | 670                 |
| Inner well width:                        | 1630                |
| Inner well depth:                        | 535                 |
| Inner well height:                       | 215                 |
| Number of removal flaps:                 | 20                  |
| Annual energy consumption kWh:           | 2233,8000           |
| Energy efficiency index:                 | 42,4665             |
| Voltage volt:                            | 230                 |
| Frequency Hz:                            | 50                  |
| Refrigeration :                          | R134a               |
| Cooling capacity:                        | 820 Watt at VT -6°C |
| Energy efficiency class :                | D                   |
| Temperature class:                       | H1 +1 +10           |
| Energy consumption kWh 24h:              | 6,1200              |
| Refrigerated display case Climate class: | 3                   |
| Standard:                                | EN ISO 23953-2      |

Typing and database errors reserved.

#### IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT  
 ☎ +43 7612 660 61  
 ✉ office@ideal-ake.at

#### AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT  
 ☎ +43 3624 211 00  
 ✉ office@ake.at