

Salatbar GN 2-1-E Single Built-in Refrigerated Display Case: self contained



€6,871.00

plus VAT

Item no.: EU386002



Glass enclosure: oblique design with normal glazing
Completely made of stainless steel, all visible sides polished
Inner well welded tight in a hygienic design
Polyurethane rigid foam insulation (compression-moulded)
Coated fin coil evaporator with circulating air – can be folded up with pressure-relief for cleaning
Speed-controlled low-voltage fan
Electronic controller with digital temperature display
Fully-automatic defrosting and condensate evaporation
Deep-drawn condensate drain HD 30
Interior lighting on the cover

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
☎ +43 7612 660 61
✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
☎ +43 3624 211 00
✉ office@ake.at

Width:	765
Depth:	695
Height:	1103
Version:	E
Power input cold:	269 Watt
Installation Opening width:	740
Installation Opening depth:	670
Inner well width:	665
Inner well depth:	535
Inner well height:	163
Annual energy consumption kWh:	946,4450
Energy efficiency index:	46,2528
Voltage volt:	230
Frequency Hz:	50
Refrigeration :	R290
Cooling capacity:	340 Watt bei VT -10°C
Energy efficiency class :	D
Temperature class:	M2 -1 +7
Energy consumption kWh 24h:	2,5930
Refrigerated display case Climate class:	3
Standard:	EN ISO 23953-2

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
 ☎ +43 7612 660 61
 ✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
 ☎ +43 3624 211 00
 ✉ office@ake.at