

## Salatbar GN 2-1-Z Single Built-in Refrigerated Display Case: remote cooling



**€5,273.00**

plus VAT

**Item no.:** EU386012



Glass enclosure: oblique design with normal glazing  
Completely made of stainless steel, all visible sides polished  
Inner well welded tight in a hygienic design  
Polyurethane rigid foam insulation (compression-moulded)  
Coated fin coil evaporator with circulating air – can be folded up with pressure-relief for cleaning  
Speed-controlled low-voltage fan  
Electronic controller with digital temperature display  
Fully-automatic defrosting and condensate evaporation  
Deep-drawn condensate drain HD 30  
Interior lighting on the cover

Typing and database errors reserved.

**IDEAL Kältetechnik GmbH**

📍 In der Schörihub 28, 4810 Gmunden, AT  
☎ +43 7612 660 61  
✉ [office@ideal-ake.at](mailto:office@ideal-ake.at)

**AKE Ausseer Kälte- und Edelstahltechnik GmbH**

📍 Pichl 66, 8984 Bad Mitterndorf, AT  
☎ +43 3624 211 00  
✉ [office@ake.at](mailto:office@ake.at)

|                                          |                       |
|------------------------------------------|-----------------------|
| Width:                                   | 765                   |
| Depth:                                   | 695                   |
| Height:                                  | 742                   |
| Version:                                 | Z                     |
| Power input cold:                        | 59 Watt               |
| Installation Opening width:              | 740                   |
| Installation Opening depth:              | 670                   |
| Inner well width:                        | 665                   |
| Inner well depth:                        | 535                   |
| Inner well height:                       | 163                   |
| Annual energy consumption kWh:           | 851,8005              |
| Energy efficiency index:                 | 45,7902               |
| Voltage volt:                            | 230                   |
| Frequency Hz:                            | 50                    |
| Refrigeration :                          | R134a                 |
| Cooling capacity:                        | 340 Watt bei VT -10°C |
| Energy efficiency class :                | D                     |
| Temperature class:                       | M2 -1 +7              |
| Energy consumption kWh 24h:              | 2,3337                |
| Refrigerated display case Climate class: | 3                     |
| Standard:                                | EN ISO 23953-2        |

Typing and database errors reserved.

#### IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT  
 ☎ +43 7612 660 61  
 ✉ office@ideal-ake.at

#### AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT  
 ☎ +43 3624 211 00  
 ✉ office@ake.at