

UKW Switch 2-1-E Combination well HOT/COLD: self-contained



€7,338.00

plus VAT

Item no.: EU500320

- Refrigerated well with switch function for quick switchover possibility between cold and hot operation optimally matched to 24/7 operation
- Air-curtain cooled well that can be used in a variety of ways for the best-possible energy efficiency in ongoing operation, guick reaction possibility to time-of-day based demand
- Heating mode: Presentation area made of black glass with underlying hotplate for optimum heat transfer to your food; a matching, switchable heated cough guard is required for this mode of operation
- Pressure-foamed inner well, welded tight in a hygienic design; wrap-around hook-in rim
- Coated, circulating air fin coil evaporator with fan, low-voltage, can be lifted up and rinsed
- Temperature control by means of ST501 control unit with temperature display, speed control of the fans, as well as on/off switch
- Fully-automatic defrosting; condensate drain HD 30; condensate drain required on-site!
- Made of high-quality stainless steel type 1.4301
- Easiest cleaning and perfect hygiene

Temperatures COLD:

Product temperature: -1°C to +7°C (Class M2)

Air temperature: +5°C Temperatures HOT:

Product temperature: > +65°C (in combination with thermal bridge)

Connected load: 769 W - 230V/50Hz DIM.: (WxDxH) 725 x 660 x 390/655 mm

Typing and database errors reserved.



Vatt
κW
a
Vatt at VT -10°C
00

Typing and database errors reserved.