

UKW Switch 3-1-E Combination well: hot/cold, self contained



€8,795.00

plus VAT

Item no.: EU500321

- Refrigerated well with switch function for quick switchover possibility between cold and hot operation optimally matched to 24/7 operation
- Air-curtain cooled well that can be used in a variety of ways for the best-possible energy efficiency in ongoing operation, quick reaction possibility to time-of-day based demand.
- Heating mode: Presentation area made of black glass with underlying hotplate for optimum heat transfer to your food; a matching, switchable heated cough guard is required for this mode of operation
- Pressure-foamed inner well, welded tight in a hygienic design; wrap-around hook-in rim
- Coated, circulating air fin coil evaporator with fan, low-voltage, can be folded up and rinsed
- Temperature control by means of ST501 control unit with temperature display, speed control of the fans, as well as on/off switch
- Fully-automatic defrosting; condensate drain HD 30; condensate drain required on-site
- Made of high-quality stainless steel type 1.4301
- Easiest cleaning and perfect hygiene

Temperatures COLD:

Product temperature: -1°C to +7°C (Class M2)

Air temperature: +5°C Tempteratures HOT:

Product temperature: > +65°C (in combination with thermal bridge)

Connected load: 1072 W - 230V/50Hz

Dimensions (WxDxH): 1050 x 660 x 390/655 mm

Typing and database errors reserved.



| Width: | 1050 |
|-----------------------------|----------------------|
| Depth: | 660 |
| Height: | 655 |
| Version: | E |
| Power input cold: | 312 Watt |
| Installation Opening width: | 1060 |
| Installation Opening depth: | 665 |
| Inner well width: | 980 |
| Inner well depth: | 535 |
| Inner well height: | 140 |
| Power input hot: | 0,76 kW |
| Voltage volt: | 230V |
| Frequency Hz: | 50Hz |
| Refrigeration : | R134a |
| Cooling capacity: | 520 Watt at VT -10°C |
| Energy consumption kWh 24h: | 17,7600 |
| | |

Typing and database errors reserved.