

W-WK 2/1-Z Combination well HOT/COLD rem. Refr.



€5,738.00

plus VAT

Item no.: EU500325

- Refrigerated well with switch function for quick switchover possibility between cold and hot operation optimally matched to 24/7 operation
- Air-curtain cooled well that can be used in a variety of ways for the best-possible energy efficiency in ongoing operation, quick reaction possibility to time-of-day based demand.
- Heating mode: Presentation area made of black glass with underlying hotplate for optimum heat transfer to your food; a matching, switchable heated cough guard is required for this mode of operation
- Pressure-foamed inner well, welded tight in a hygienic design; wrap-around hook-in rim
- Coated, circulating air fin coil evaporator with fan, low-voltage, can be folded up and rinsed
- Temperature control by means of ST501 control unit with temperature display, speed control of the fans, as well as on/off switch
- Fully-automatic defrosting; condensate drain HD 30; condensate drain required on-site
- Made of high-quality stainless steel type 1.4301
- Easiest cleaning and perfect hygiene

Temperatures COLD:

Product temperature: -1°C to +7°C (Class M2)

Air temperature: +5°C Tempteratures HOT:

Product temperature: > +65°C (in combination with thermal bridge)

Connected load: 500 W - 230V/50Hz Refrigeration capac.: 370 W at ET -10°C Dimensions (WxDxH): 725 x 660 x 390 mm

Typing and database errors reserved.



| Width: | 725 |
|-----------------------------|----------------------|
| Depth: | 660 |
| Height: | 390 |
| Version: | Z |
| Power input cold: | 12 Watt |
| Installation Opening width: | 735 |
| Installation Opening depth: | 665 |
| Inner well width: | 655 |
| Inner well depth: | 535 |
| Inner well height: | 140 |
| Power input hot: | 0,51 kW |
| Voltage volt: | 230V |
| Frequency Hz: | 50Hz |
| Refrigeration : | R134a |
| Cooling capacity: | 390 Watt at VT -10°C |
| | |

Typing and database errors reserved.