W-WK 4/1-Z Combination well HOT/COLD rem. Refr.



€8,825.00

plus VAT

Item no.: EU500327

- Refrigerated well with switch function for quick switchover possibility between cold and hot operation – optimally matched to 24/7 operation
- Air-curtain cooled well that can be used in a variety of ways for the best-possible energy efficiency in ongoing operation, quick reaction possibility to time-of-day based demand.
- Heating mode: Presentation area made of black glass with underlying hotplate for optimum heat transfer to your food; a matching, switchable heated cough guard is required for this mode of operation
- Pressure-foamed inner well, welded tight in a hygienic design; wrap-around hook-in rim
- Coated, circulating air fin coil evaporator with fan, low-voltage, can be folded up and rinsed
- Temperature control by means of ST501 control unit with temperature display, speed control of the fans, as well as on/off switch
- Fully-automatic defrosting; condensate drain HD 30; condensate drain required on-site
- Made of high-quality stainless steel type 1.4301
- Easiest cleaning and perfect hygiene

Temperatures COLD:
Product temperature: -1°C to +7°C (Class M2)
Air temperature: +5°C
Tempteratures HOT:
Product temperature: > +65°C (in combination with thermal bridge)

Connected load: 1024 W – 230V/50Hz
Refrigeration capac.: 600 W at ET -10°C
Dimensions (WxDxH): 1375 x 660 x 390 mm

Typing and database errors reserved.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at

Width:	1375
Depth:	660
Height:	390
Version:	Z
Power input cold:	14 Watt
Installation Opening width:	1385
Installation Opening depth:	665
Inner well width:	1305
Inner well depth:	535
Inner well height:	140
Power input hot:	1,01 kW
Voltage volt:	230V
Frequency Hz:	50Hz
Refrigeration :	R134a
Cooling capacity:	600 Watt at VT -10°C

Typing and database errors reserved.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at