

KGU GR-152-70-Z Combo display,cold - not refrigerated: remote cooling



€8,488.00

plus VAT

Item no.: EU510366

CURVED Entirely made of stainless steel, 24 Volt fan. Service side: Refr. part with sliding, insulated glass doors (left), ambient part open (right); Customer side: panorama glass pane made of safety glass; 2 shelves per part made of glass adjustable in height, internal lighting on each level, incl. deep well with base trays adjustable in height, incl. control unit with digital temperature display. Expansion valve R 134a mounted, outlets for pipes on the bottom. Drain necessary. Temperature: Air 5°C / Product M2 / 3 Refrigerant: R 134a Refrigerating capacity: 480 Watt at ET -8°C Dim.: (WxDxH) 1525x695x700/1070 mm

| | |
|-----------------------------|---------------------|
| Modell: | curved |
| Width: | 1525 |
| Depth: | 695 |
| Height: | 1070 |
| Version: | Z |
| Power input cold: | 137 Watt |
| Installation Opening width: | 1065 |
| Installation Opening depth: | 670 |
| Voltage volt: | 230 |
| Frequency Hz: | 50 |
| Refrigeration : | R134a |
| Cooling capacity: | 520 Watt at VT -8°C |
| Energy consumption kWh 24h: | 5,3800 |

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT

☎ +43 7612 660 61

✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT

☎ +43 3624 211 00

✉ office@ake.at