

KGW GS-160-70-E DIAMANT Combination display case - COLD/HOT

€12,950.00

plus VAT

Item no.: EU512381

SLANTED Entirely made of stainless steel, coated evaporator, fully automatic defrosting and evaporation of condense water, ventilated cooling unit bolted to the base of the unit; Service side: Refr. part with sliding doors made of insulated glass (left), hot part with folding door made of insulated glass (right); Customer side: panorama glass pane made of safety glass. Cold part: 2 shelves made of glass adjustable in height, internal lighting on each level, incl. deep well with base trays adjustable in height. Hot part: 1 shelf, display surface able for GN 1/1 trays with a depth of 100 mm. Incl. control unit with digital temperature display. Temperature range COLD: Air 5°C / Product M2 / 3 Temperature range HOT: +65°C to +85°C Voltage: 203 V / 50 Hz, 598 Watt Dim.: (WxDxH) 1600x695x700/1375 mm

Modell:	inclined
Width:	1600
Depth:	695
Height:	1375
Version:	E
Power input cold:	391 Watt
Installation Opening width:	1550
Installation Opening depth:	670
Power input hot:	940 W
Voltage volt:	230V
Frequency Hz:	50Hz
Refrigeration :	R134a
Cooling capacity:	520 Watt at VT -8°C
Energy consumption kWh 24h:	4,9600

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
 ☎ +43 7612 660 61
 ✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
 ☎ +43 3624 211 00
 ✉ office@ake.at