KGW GS-160-70-E R290 Combo display cold/hot: self-contained



€12,950.00

plus VAT

Item no.: EU535471

Glass enclosure: oblique design with normal glazing
Left: refrigerated section – Right: Hot section with central partition made of insulating glass
Completely made of stainless steel, all visible sides polished
Inner well welded tight in a hygienic design
Polyurethane rigid foam insulation (compression-moulded)
Speed-controlled low-voltage fan
Supporting heat including heat-resistant lighting per presentation area
Electronic controller with digital temperature display
Fully-automatic defrosting
Deep-drawn condensate drain HD 30
Interior lighting on each level
Price tag holder on all presentation levels

Typing and database errors reserved.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at

Modell:	inclined
Width:	1600
Depth:	695
Height:	1375
Version:	E
Power input cold:	292 Watt
Installation Opening width:	1550
Installation Opening depth:	670
Power input hot:	0,93 kW
Voltage volt:	230V
Frequency Hz:	50Hz
Refrigeration :	R290
Cooling capacity:	490 Watt at VT -6°C
Temperature class:	H1 +1 +10

Typing and database errors reserved.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at