

UKW Switch 3-1-E R290 Slide In with pedestal: self contained



€9,595.00

plus VAT

Item no.: EU535551



Refrigerated well with switch function for quick switchover possibility between cold and hot operation (optimally adjusted for 24/7 operation)

Completely made of stainless steel, all visible sides polished

Inner well welded tight in a hygienic design

Polyurethane rigid foam insulation (compression-moulded)

Coated fin coil evaporator with circulating air - can be folded up for cleaning

Speed-controlled low-voltage fan

Electronic controller with digital temperature display

Fully-automatic defrosting

Deep-drawn condensate drain HD 30

NOTE: Optimal operation of this appliance is ensured in combination with a hot cough guard incl. lighting (WB HS)

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT

☎ +43 7612 660 61

✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT

☎ +43 3624 211 00

✉ office@ake.at

Width:	1090
Depth:	695
Height:	910
Version:	E
Power input cold:	224 Watt
Installation Opening width:	1060
Installation Opening depth:	665
Inner well width:	980
Inner well depth:	535
Inner well height:	140
Power input hot:	0,76 kW
Annual energy consumption kWh:	1306,3350
Energy efficiency index:	58,7824
Voltage volt:	230V
Frequency Hz:	50Hz
Refrigeration :	R290
Cooling capacity:	490 Watt at VT -6°C
Energy efficiency class :	E
Temperature class:	M2 -1 +7
Energy consumption kWh 24h:	3,5790
Refrigerated display case Climate class:	3
Standard:	EN ISO 23953-2

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
 ☎ +43 7612 660 61
 ✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
 ☎ +43 3624 211 00
 ✉ office@ake.at