UKW Switch 2-1-Z Switchable display case: remote cooling



€5,952.00

plus VAT

Item no.: EU535555



Refrigereted well with switch function for quick switchover possibility between cold and hot operation (optimally adjusted for 24/7 operation)
Completely made of stainless steel, all visible sides polished
Inner well welded tight in a hygienic design
Polyurethane rigid foam insulation (compression-moulded)
Coated fin coil evaporator with circulating air - can be folded up for cleaning
Speed-controlled low-voltage fan
Electronic controller with digital temperature display
Fully-automatic defrosting
Deep-drawn condensate drain HD 30
NOTE: Optimal operation of this appliance is ensured in combination with a hot cough guard incl. lighting (WB HS)

Typing and database errors reserved.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at

Width:	765
Depth:	695
Height:	390
Version:	Z
Power input cold:	12 Watt
Installation Opening width:	735
Installation Opening depth:	665
Inner well width:	655
Inner well depth:	535
Inner well height:	140
Power input hot:	0,51 kW
Annual energy consumption kWh:	1113,2500
Energy efficiency index:	61,9113
Voltage volt:	230V
Frequency Hz:	50Hz
Refrigeration :	R134a
Cooling capacity:	390 Watt at VT -10°C
Energy efficiency class :	E
Temperature class:	M2 -1 +7
Energy consumption kWh 24h:	3,0500
Refrigerated display case Climate class:	3
Standard:	EN ISO 23953-2

Typing and database errors reserved.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at