

Switch GS-80-45-E EC R290 Slide In with pedestal: self contained



€11,031.00

plus VAT

Item no.: EU535580



Glass enclosure: oblique design with normal glazing
Display case with switch function for quick switchover possibility between cold and hot operation (optimally adjusted for 24/7 operation)
Completely made of stainless steel, all visible sides polished
For suspension with mounting frame
Inner well welded tight in a hygienic design
Polyurethane rigid foam insulation (compression-moulded)
Coated fin coil evaporator with circulating air or Hotplate with black glass display - can be folded up for cleaning
Speed-controlled low-voltage fan
Electronic controller with digital temperature display
Fully-automatic defrosting
Deep-drawn condensate drain HD 30
Interior lighting in combination with supporting heat
Cleaning-friendly light-glass enclosure

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
☎ +43 7612 660 61
✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
☎ +43 3624 211 00
✉ office@ake.at

Width:	800
Depth:	695
Height:	1345
Version:	E
Power input cold:	151 Watt
Power input hot:	0,51 kW
Annual energy consumption kWh:	1113,2500
Energy efficiency index:	56,2830
Voltage volt:	230V
Frequency Hz:	50Hz
Refrigeration :	R290
Cooling capacity:	340 Watt bei VT-6°C
Energy efficiency class :	E
Temperature class:	M2 -1 +7
Energy consumption kWh 24h:	3,0500
Refrigerated display case Climate class:	3
Standard:	EN ISO 23953-2

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
 ☎ +43 7612 660 61
 ✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
 ☎ +43 3624 211 00
 ✉ office@ake.at