Switch Flaps 70-Z Switchable disp. case w. flip-up d. - remote refr.



€9,916.00

plus VAT

Item no.: EU538635

- Self-service display case with switch function for quick switchover possibility between cold and hot operation – optimally matched to 24/7 operation
- Heating mode: With infrared supporting heat and primary heat below the black glass presentation area – settable by means of pictogram control
- Cooling mode: Air-curtain cooled display case for the best-possible energy efficiency in ongoing operation, temperature control by means of a control unit with temperature display,
- Inclined positioning of the intermediate shelf made of black glass for first-class view of the product assortment and optimum temperature transmission to the products
- Soft-close removal flaps made of tempered safety glass with integrated soft-close system for convenient food removal; optimum spit and cough protection and the best energy efficiency
- Hinged door on operator side made of insulated glass with two-way mirror
- glass build up made of tempered safety glass
- Transparent construction
- Long-lasting LED lighting per level
- Easiest cleaning and perfect hygiene
- Remote refrigeration: expansion valve R134a, connection lines lead out downwards, drain required on-site for remote refrigeration, control unit (250x185x175mm) and display cover (290x70mm) loose

Temperatures COLD:
Product temperature: -1°C to +7°C (Class M2)
Air temperature: +5°C

Typing and database errors reserved.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at

Tempteratures HOT:
Product temperature: > +65°C

Connected load: 1700 W – 230V/50Hz
Refrigeration capac.: 420 W at ET -8°C
Dimensions (WxDxH): 600 x710 x 700/960 mm

Width:	600
Depth:	710
Height:	960
Version:	Z
Installation Opening width:	580
Installation Opening depth:	670
Inner well width:	490
Inner well depth:	535
Inner well height:	75
Power input hot:	1,1 kW
Voltage volt:	230
Frequency Hz:	50
Refrigeration :	R134a

Typing and database errors reserved.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at