

Tropical Switch Flaps 80-87-E Switchable disp. case w. flip-up d. - self cont.



€14,824.00

plus VAT

Item no.: EU539931

- Self-service display case with switch function for quick switchover possibility between cold and hot operation – optimally matched to 24/7 operation
- Display case that can be used in a variety of ways for the presentation of cold or hot snacks on multiple levels
- No condensate formation on the soft-close removal flaps thanks to the integrated window ventilation (double air-curtain)
- Heating mode: With infrared supporting heat and primary heat below the black glass presentation area – settable by means of pictogram control
- Cooling mode: Air-curtain cooled display case for the best-possible energy efficiency in ongoing operation, temperature control by means of a control unit with temperature display,
- Inclined positioning of the intermediate shelf made of black glass for first-class view of the product assortment and optimum temperature transmission to the products
- Soft-close removal flaps made of tempered safety glass with integrated soft-close system for convenient food removal; optimum spit and cough protection and the best energy efficiency
- Hinged door on operator side made of insulated glass with two-way mirror
- Side windows made of insulating glass
- Transparent construction
- Long-lasting LED lighting per level
- Easiest cleaning and perfect hygiene
- Self-contained: With refrigerant R134a; fully automatic condensate evaporation for self-contained model;

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
☎ +43 7612 660 61
✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
☎ +43 3624 211 00
✉ office@ake.at

Temperatures COLD:

Product temperature: -1°C to +5°C (Class M1)

Air temperature: +2°C

Temperatures HOT:

Product temperature: > +65°C

Connected load: 2060 W - 230V/50Hz

Dimensions (WxDxH): 800 x710 x 870/1505 mm

Width:	800
Depth:	710
Height:	1505
Version:	E
Installation Opening width:	780
Installation Opening depth:	670
Power input hot:	2,07 kW
Voltage volt:	230
Frequency Hz:	50
Refrigeration :	R134a
Cooling capacity:	590 Watt at VT -8°C

Typing and database errors reserved.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT

☎ +43 7612 660 61

✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT

☎ +43 3624 211 00

✉ office@ake.at