

## Forced-air cooling wells GN

### Self-contained and remote refrigeration

Multifunctional refrigerated well with convection cooling that cools the goods gently with an air curtain. 3-piece, inner well in hygienic design can be removed for cleaning. For use with Gastronorm trays or baking trays as well as for bottles or crushed ice.

- **Design:** Chromium nickel steel on the outside and inside, all visible sides polished. Inner edges welded tight with deep-drawn condensate drain HD 30. Refrigerated well to be hooked in with a hook-in rim and installation frame or for installation underneath the countertop. Air baffle can be tilted and unhooked. With height-adjustable base decks as standard.
- **Insulation:** Polyurethane rigid foam (compression-moulded).
- **Refrigeration system:** Large, coated fin coil evaporator with circulating air, can be folded up for cleaning. Low-voltage fans, enabling hazard-free rinsing of the evaporator, fans and inner well with the hand spray. Control unit with digital temperature display including speed control of the fans, as well as on/off switch. Removable display for installation in the front of the unit (2 m cable). Condensate drain required on-site or condensate tray as an option.
- **Self-contained:** Forced air circulation refrigeration unit in compressor compartment below, can be pulled out for service purposes.
- **Remote refrigeration:** Expansion valve installed for R134a, connection lines lead out downwards.
- **Air temperature:** +4 °C
- **Product:** 3M2

## Forced-air cooling wells EURO

### Self-contained and remote refrigeration

Multifunctional refrigerated well with convection cooling that cools the goods gently with an air curtain. 3-piece, inner well in hygienic design can be removed for cleaning. For use with Euronorm baking trays as well as for bottles or crushed ice.

- **Design:** Chromium nickel steel on the outside and inside, all visible sides polished. Inner edges welded tight with deep-drawn condensate drain HD 30. Refrigerated well to be hooked in with a hook-in rim and installation frame or for installation underneath the countertop. Air baffle can be tilted and unhooked. With height-adjustable base decks as a standard, 400 x 600 mm.
- **Insulation:** Polyurethane rigid foam (compression-moulded)
- **Refrigeration system:** Large, coated fin coil evaporator with circulating air, can be folded up for cleaning. Low-voltage fans, enabling hazard-free rinsing of the evaporator, fans and inner well with the hand spray. Control unit with digital temperature display including speed control of the fans, as well as on/off switch. Removable display for installation in the front of the unit (2 m cable). Condensate drain required on-site or condensate tray as an option.
- **Self-contained:** Forced air circulation refrigeration unit in compressor compartment below, can be pulled out easily for service purposes.
- **Remote refrigeration:** Expansion valve installed for R134a, connection lines lead out downwards.
- **Air temperature:** +4 °C
- **Product:** 3M2