

Only available on request

BAKERY combo

Self-contained and remote refrigeration

Multifunctional built-in refrigerated service counter with convection cooling that cools the goods gently with an air curtain. Presentation area in a hygienic design, possible to combine with GN trays (100 mm) and baking trays.

- **Design:** Chromium nickel steel on the outside and inside, all visible sides polished. Inner edges welded tight with deep-drawn condensate drain HD 30. Refrigerated well to be hooked in with a hook-in rim and installation frame or for installation underneath the countertop. The refrigerated service counter with convection cooling is only functional with at least a 3-sided glass enclosure.
 - **Insulation:** Polyurethane rigid foam (compression-moulded).
 - **Refrigeration system:** Large, coated, circulating air fin coil evaporator with presentation area, spring balancer offloaded, can be folded up for cleaning. Low-voltage fans, enabling hazard-free rinsing of the evaporator, fans and inner well with the hand spray. Control unit with digital temperature display including speed control of the fans, as well as on/off switch. Removable display for installation in the front of the unit (2 m cable). Condensate drain required on-site or condensate tray as an option.
 - **Self-contained:** Forced air circulation refrigeration unit in compressor compartment below, can be pulled out for service purposes.
 - **Remote refrigeration:** Expansion valve installed for R134a, connection lines lead out downwards.
 - **Air temperature:** +4 °C
- Product:** 3M2

BAKERY 8° inclined

Self-contained and remote refrigeration

Multifunctional inclined built-in refrigerated service counter with convection cooling that cools the goods gently with an air curtain. For the use of Euronorm baking trays, 400 x 600 mm. Presentation area can be inclined by 8°.

- **Design:** Chromium nickel steel on the outside and inside, all visible sides polished. Inner edges welded tight with deep-drawn condensate drain HD 30. Refrigerated well to be hooked in with a hook-in rim and installation frame or for installation underneath the countertop. The refrigerated service counter with convection cooling is only functional with at least a 3-sided glass enclosure.
 - **Insulation:** Polyurethane rigid foam (compression-moulded).
 - **Refrigeration system:** Large, coated, circulating air fin coil evaporator with presentation area, spring balancer offloaded, can be folded up for cleaning. Low-voltage fans, enabling hazard-free rinsing of the evaporator, fans and inner well with the hand spray. Control unit with digital temperature display including speed control of the fans, as well as on/off switch. Removable display for installation in the front of the unit (2 m cable). Condensate drain required on-site or condensate tray as an option.
 - **Self-contained:** Forced air circulation refrigeration unit in compressor compartment below, can be pulled out for service purposes.
 - **Remote refrigeration:** Expansion valve installed for R134a, connection lines lead out downwards.
 - **Air temperature:** +4 °C
- Product:** 3M2