

## Cool Bottle – Grab & Go

Self-service refrigerated display case for the attractive presentation and convenient removal of chilled beverages and packaged products

- **Perfect View:** First-class overview of the entire product range thanks to the inclined presentation level. Product slide: Always well-filled sales front thanks to automatic replenishment of the bottles after product removal – positive effect through perception of a full assortment. Variable hook-in frames to adapt to the different dimensions of the goods.  
Attractive product presentation thanks to LED lighting with natural colour reproduction.  
Fully extractable drawer on the operator side for easy and uncomplicated stocking, quick refilling or a quick change of products – to be able to react immediately to customer demands based on the time of day.
- **Quick Cleaning:** Cleaning in no time at all thanks to the removable bottle slider, easy to remove hook-in frame, removable drawer and lift-up evaporator. Combination unit for all FOODS-TATION Flaps and can also be used stand-alone.
- **Design:** Completely made of stainless steel, all visible sides polished; inner well welded tight in a hygienic design; polyurethane rigid foam insulation (compression-moulded); with refrigerated base.
- **Operator side:** Fully-extractable drawer including product slider (chute system).
- **Customer side:** Open (grab & go) with glass edging.
- **Refrigeration system:** Large, coated fin coil evaporator with circulating air, can be folded up for cleaning and rinsing. Low-voltage fans, enabling hazard-free rinsing of the evaporator, fans and inner well with the hand spray. Control unit with digital temperature display including speed control of the fans, as well as on/off switch. Removable display for installation in the front of the unit (2 m cable).
- **Self-contained:** Fully automatic defrosting and condensate evaporation; forced air circulation refrigeration unit in side compressor compartment; installation lines lead into the side installation compartment.
- **Remote refrigeration:** Expansion valve installed for R134a, connection lines lead out to the side. Condensate drain required on-site or condensate tray as an option.
- **Air temperature:** +5 °C
- **Product:** 3M2