

Built-in refrigerated display case Green

Self-contained and remote refrigeration

- **Design:** Stainless steel on the outside and inside, all visible sides polished. Inner well welded tight in a hygienic design with deep-drawn condensate drain HD 30, full-perimeter hook-in rim. Side windows made of insulating glass. Height-adjustable, inclining, intermediate shelves made of tempered safety glass. Height-adjustable base decks. Interior lighting (LED) per level placed horizontally and protected, LED lamps. Interior suitable for GN 1/1.
- **Insulation:** Polyurethane rigid foam (compression-moulded).
- **Operator side:** Sliding doors made of insulating glass, without bottom track.
- **Customer side:** Panoramic window made of insulating glass – removable.
- **Refrigeration system:** Large, coated fin coil evaporator with circulating air, can be folded up for cleaning. Low-voltage fans, enabling hazard-free rinsing of the evaporator, fans and inner well with the hand spray. Control unit with digital temperature display including speed control of the fans, as well as on/off switch. Removable display for installation in the front of the unit (2 m cable).
- **Self-contained:** Fully automatic defrosting and condensate evaporation. Forced air circulation refrigeration unit in compressor compartment below, easily accessible for service purposes.
- **Remote refrigeration:** Expansion valve installed for R134a, connection lines lead out downwards. Condensate drain required on-site or condensate tray as an option.
- **Air temperature:** +2 °C
- **Product:** 3M1

Built-in refrigerated display case, cake drawer Green L

Self-contained and remote refrigeration

- **Design:** Stainless steel on the outside and inside, all visible sides polished. Inner well welded tight in a hygienic design with deep-drawn condensate drain HD 30. Side windows made of insulating glass. Height-adjustable, inclining intermediate shelf made of tempered safety glass. Interior lighting (LED) per level placed horizontally and protected, LED lamps.
- **Insulation:** Polyurethane rigid foam (compression-moulded).
- **Operator side:** Sliding doors made of insulating glass without bottom track, as well as 1 full-extension drawer for 1.5/2.5 or alternatively 3 EN baking trays
- **Customer side:** Panoramic window made of insulating glass – removable
- **Refrigeration system:** Large, coated fin coil evaporator with circulating air, can be folded up for cleaning; Low-voltage fans, enabling hazard-free rinsing of the evaporator, fans and inner well with the hand spray. Control unit with digital temperature display including speed control of the fans, as well as on/off switch. Removable display for installation in the front of the unit (2 m cable).
- **Self-contained:** Fully automatic defrosting and condensate evaporation. Forced air circulation refrigeration unit in compressor compartment below, easily accessible for service purposes.
- **Remote refrigeration:** Expansion valve installed for R134a, connection lines lead out downwards. Condensate drain required on-site or condensate tray as an option.
- **Air temperature:** +2 °C
- **Product:** 3M1