

VARIO presenter

Self-contained and remote refrigeration

- **Design:** Stainless steel on the outside and inside, all visible sides polished. Inner well welded tight in a hygienic design with deep-drawn condensate drain HD 30, full-perimeter hook-in rim. Side windows, front glass and glass cover made of insulating glass – imprinted. Intermediate shelves made of tempered safety glass. Interior lighting (LED) per level placed horizontally and protected, LED lamps.
- **Insulation:** Polyurethane rigid foam (compression-moulded).
- **Glass enclosure:** Squared design with double-glazing, completely made of stainless steel, all visible sides polished; inner well welded tight in a hygienic design; polyurethane rigid foam insulation.
- **Refrigeration system:** Large, coated fin coil evaporator with circulating air, can be folded up for cleaning. Low-voltage fans, enabling hazard-free rinsing of the evaporator, fans and inner well with the hand spray. Control unit with digital temperature display including speed control of the fans, as well as on/off switch. Removable display for installation in the front of the unit (2 m cable).
- **Self-contained:** Fully automatic defrosting and condensate evaporation. Forced air circulation refrigeration unit in compressor compartment below, easily accessible for service purposes.
- **Remote refrigeration:** Expansion valve installed for R134a, connection lines lead out downwards. Condensate drain required on-site or condensate tray as an option.
- **Air temperature:** +2 °C
- **Product:** 3M1

Temporarily not available. Please request!

Countertop display cases HMV and SAV

Self-contained or remote refrigeration; Customer side: straight or inclined 10°, with insulating glass or soft-close removal flaps

- **Design:** Completely made of chromium nickel steel 1.4301, all visible sides polished; side windows made of insulating glass; Height-adjustable intermediate shelves made of tempered safety glass; LED interior lighting horizontal and protected, placed below the unit's cover; Standard colour of the lamp is white; Optionally stilted on pedestal; Side and back wall optionally available in CNS; Colour coating possible as an option
- **Operator side:** Sliding doors made of insulating glass, with safety catch, without bottom track; Optionally lockable; Optionally with soft-close removal flaps made of acrylic glass
- **Customer side:** Insulating glass or soft-close flaps made of acrylic glass; Optionally available with sliding doors; Optionally lockable. Refrigeration system: Large, coated fin coil evaporator with circulating air below the unit's cover; Low-voltage fan; Fully automatic air defrost
- **Controller:** Intelligent electronic IDEAL controller with plain text display; Display can be installed separately; Easy replacement of the display during operation; Ergonomic button arrangement; Robust against water spray and cleaning agents; Smooth speed control of the fans possible; Timing of the frame heater; Error detection and display in plain text; Early-warning system on the compressor for high level of safeguarding against failure; Third-party controllers can be installed as an option.
- **Lighting:** Brilliant display case lighting for an attractive product presentation; Long-lasting, heat-resistant LED lighting with natural colour reproduction ensures good and energy-saving illumination of your products; LEDs installed under the cover; Standard lamp colour is 4000 K
- **Self-contained:** Compressor compartment installed on countertop display case on the left, right or below at any position; Forced air circulation refrigeration unit installed in the compressor compartment; integrated, separate, pull-out condensate evaporation tray for cleaning.
- **Compressor installed below:** Removable ventilation grille; integrated, separate, pull-out condensate evaporation tray for cleaning.
- **Remote refrigeration:** Expansion valve installed for R134a as standard; connection lines lead out downwards on the operating side; condensate drain required on-site.
- **Refrigerant:** R134a
- **Temperature range:**
- **Air temperature:** +2 °C
- **Product:** 3M1
Specifications for ambient temperature of + 25 °C and rel. air humidity of 60% (climate class 3 in compliance with OENORM EN ISO 23953-2)