

## Built-in combo display case KGW

### Self-contained and remote refrigeration

- **Design:** Stainless steel on the outside and inside, all visible sides polished. Inner well welded tight in a hygienic design with deep-drawn condensate drain HD 30, full-perimeter hook-in rim. Side windows and height-adjustable intermediate shelves made of tempered safety glass. Height-adjustable base decks. Interior lighting per level placed horizontally and protected LED lamps.
- **Insulation:** Polyurethane rigid foam (compression-moulded).
- **Operator side:** Refrigerated section with sliding doors made of insulating glass – without bottom track. Heated section with hinged door.
- **Customer side:** Panoramic window made of tempered safety glass – removable
- **Heated display case design:** Completely made of stainless steel, all visible sides polished, glass cover made of tempered safety glass, full perimeter hook-in rim, electronic controller; LED lamps.
- **Operator side:** Removable hinged doors made of one-way mirror.
- **Heat source:** Hotplate (primary heat) on the bottom; supporting heat including heat-resistant lighting on the cover – ensures that the required core temperature is maintained.
- **Presentation area:** Possible to stock the well with a maximum tray height up to 100 mm; perforated hook-in frame for GN trays including dividing bar.
- **Temperature range:** > 65 °C
- **Refrigeration system:** Refrigerant: R 134a
- Large, coated fin coil evaporator with circulating air, can be folded up for cleaning. Low-voltage fans, enabling hazard-free rinsing of the evaporator, fans and inner well with the hand spray. Control unit with digital temperature display including speed control of the fans, as well as on/off switch. Removable display for installation in the front of the unit (2 m cable – only refrigerated section).
- **Self-contained:** Forced air circulation refrigeration unit installed in the compressor compartment below, can be pulled out for service purposes; fully automatic defrosting and condensate evaporation.
- **Remote refrigeration:** Expansion valve installed for R134a, connection lines lead out downwards. Condensate drain required on-site or condensate tray as an option.
- **Tub:**  
**Air temperature:** +5 °C  
**Product:** 3M2
- **Shelf:**  
**Product:** 3H1

## Built-in combo display case KGU

### Self-contained and remote refrigeration

- **Design:** Stainless steel on the outside and inside, all visible sides polished. Inner well welded tight in a hygienic design with deep-drawn condensate drain HD 30, full-perimeter hook-in rim. Side windows and height-adjustable intermediate shelves made of tempered safety glass. Height-adjustable base decks. Interior lighting per level placed horizontally and protected LED lamps
- **Insulation:** Polyurethane rigid foam (compression-moulded).  
Operator side: Refrigerated section with sliding doors made of insulating glass – without bottom track. Unrefrigerated section open.
- **Customer side:** Panoramic window made of tempered safety glass – removable
- **Refrigeration system:** Large, coated fin coil evaporator with circulating air, can be folded up for cleaning. Low-voltage fans, enabling hazard-free rinsing of the evaporator, fans and inner well with the hand spray. Control unit with digital temperature display including speed control of the fans, as well as on/off switch. Removable display for installation in the front of the unit (2 m cable).
- **Self-contained:** Forced air circulation refrigeration unit installed in the compressor compartment below, can be pulled out for service purposes; fully automatic defrosting and condensate evaporation.
- **Remote refrigeration:** Expansion valve installed for R134a, connection lines lead out downwards. Condensate drain required on-site or condensate tray as an option.
- **Tub:**  
**Air temperature:** +5 °C  
**Product:** 3M2
- **Shelf:**  
**Product:** 3H1