UKW Switch 3-1-E Combination well: hot/cold, self contained



8 795,00 €

hors TVA

Réf. d'article : EU500321

- Refrigerated well with switch function for quick switchover possibility between cold and hot operation – optimally matched to 24/7 operation
- Air-curtain cooled well that can be used in a variety of ways for the best-possible energy efficiency in ongoing operation, quick reaction possibility to time-of-day based demand.
- Heating mode: Presentation area made of black glass with underlying hotplate for optimum heat transfer to your food; a matching, switchable heated cough guard is required for this mode of operation
- Pressure-foamed inner well, welded tight in a hygienic design; wrap-around hook-in rim
- Coated, circulating air fin coil evaporator with fan, low-voltage, can be folded up and rinsed
- Temperature control by means of ST501 control unit with temperature display, speed control of the fans, as well as on/off switch
- Fully-automatic defrosting; condensate drain HD 30; condensate drain required on-site
- Made of high-quality stainless steel type 1.4301
- Easiest cleaning and perfect hygiene

Temperatures COLD:
Product temperature: -1°C to +7°C (Class M2)
Air temperature: +5°C
Tempteratures HOT:
Product temperature: > +65°C (in combination with thermal bridge)

Connected load: 1072 W – 230V/50Hz
Dimensions (WxDxH): 1050 x 660 x 390/655 mm

Erreurs, changements et omissions réservés.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at

Largeur:	1050
Profondeur:	660
Hauteur:	655
Version:	E
Puissance absorbée froide:	312 Watt
Ouverture de montage largeur:	1060
Ouverture de montage profondeur:	665
Cuve intérieure largeur:	980
Cuve intérieure profondeur:	535
Cuve intérieure hauteur:	140
Puissance absorbée chaude:	0,76 kW
Voltage Volt:	230V
Fréquence Hz:	50Hz
Fluide frigorigène:	R134a
Capacité frigorifique:	520 Watt à TE -10°C
Consommation d'énergie kWh 24h:	17,7600

Erreurs, changements et omissions réservés.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at